

Page 1/10

Revision: 05.12.2024

Tel.: +49 (0)800 4372522

#### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.12.2024

Version number 5 (replaces version 3)

# SECTION 1: Identification of the substance/mixture and of the company

#### undertaking · 1.1 Product identifier

- · Trade name: Signum metal bond I
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
  - · Application of the substance / the mixture Metal-Resin Bonding System
- · 1.3 Details of the supplier of the safety data sheet
  - Manufacturer/Supplier:

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

· Informing department: E-Mail: msds@kulzer-dental.com

• 1.4 Emergency telephone number: Emergency CONTACT (24-Hour-Number): +49 (0)6132-84463

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
  - Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
  - Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

acetone

· Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. P210

No smoking.

P261 Avoid breathing mist/vapours/spray. P280 Wear protective gloves / eye protection.

P337+P313 If eye irritation persists: Get medical advice/attention.

#### Additional information:

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

· 2.3 Other hazards -

(Contd. on page 2)



Page 2/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.12.2024 Version number 5 (replaces version 3) Revision: 05.12.2024

# Trade name: Signum metal bond I

(Contd. of page 1)

- · Results of PBT and vPvB assessment
  - · **PBT:** Not applicable. · **vPvB:** Not applicable.

### **SECTION 3: Composition/information on ingredients**

- · 3.2 Mixtures
  - · Description: -

· Dangerous components:	Dangerous components:		
EINECS: 200-662-2 Index number: 606-001-00-8	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	>90%	
	10-(Phosphonooxy)decyl methacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	0-5%	
EINECS: 200-580-7 Index number: 607-002-00-6	acetic acid Flam. Liq. 3, H226 Skin Corr. 1A, H314; Eye Dam. 1, H318 'Specific concentration limits: Skin Corr. 1A; H314: C ≥ 90 % Skin Corr. 1B; H314: 25 % ≤ C < 90 % Skin Irrit. 2; H315: 10 % ≤ C < 25 % Eye Irrit. 2; H319: 10 % ≤ C < 25 %	≥1-<3%	

<sup>·</sup> Additional information For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
  - · After inhalation Supply fresh air; consult doctor in case of symptoms.
  - · After skin contact

Instantly rinse with water.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

· After swallowing

Rinse out mouth and then drink plenty of water.

In case of persistent symptoms consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

GB



Page 3/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.12.2024

Version number 5 (replaces version 3)

Revision: 05.12.2024

# Trade name: Signum metal bond I

(Contd. of page 2)

### SECTION 5: Firefighting measures

- 5.1 Extinguishing media
  - · Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

- For safety reasons unsuitable extinguishing agents Water with a full water jet.
- 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
  - · Protective equipment:

Wear self-contained breathing apparatus.

Wear full protective suit.

· Additional information -

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Avoid contact with eyes and skin.

Use breathing protection against the effects of fumes/dust/aerosol.

- · 6.2 Environmental precautions: Prevent material from reaching sewage system, holes and cellars.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).

Ensure adequate ventilation.

Send for recovery or disposal in suitable containers.

6.4 Reference to other sections

See Section 13 for information on disposal.

See Section 8 for information on personal protection equipment.

-

### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
  - · Storage
    - Requirements to be met by storerooms and containers: Store in cool location.
    - Information about storage in one common storage facility: Not required.
    - · Further information about storage conditions:
  - Store in cool, dry conditions in well sealed containers.
- · 7.3 Specific end use(s) No further relevant information available.

GB



Page 4/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.12.2024 Version number 5 (replaces version 3) Revision: 05.12.2024

Trade name: Signum metal bond I

(Contd. of page 3)

# SECTION 8: Exposure controls/personal protection 8.1 Control parameters Components with critical values that require monitoring at the workplace:

components with childen values that require monitoring at the workplace.		
67-64-1 acetone		
WEL (Great Britain)	Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm	
IOELV (European Union)	Long-term value: 1210 mg/m³, 500 ppm	
64-19-7 acetic acid		
WEL (Great Britain)	Short-term value: 50 mg/m³, 20 ppm Long-term value: 25 mg/m³, 10 ppm	
IOELV (European Union)	Short-term value: 50 mg/m³, 20 ppm Long-term value: 25 mg/m³, 10 ppm	

· DNELs			
67-64-1 acetone			
Oral	general population, long term, systemic	62 mg/Kg (not defined)	
Dermal	worker industrial, long term, systemic	186 mg/Kg/d (not defined)	
	general population, long term, systemic	62 mg/Kg/d (not defined)	
Inhalative	worker industrial, long term, systemic	1,210 mg/m3 (not defined)	
	worker industrial, long term, local	2,420 mg/m3 (not defined)	
	general population, long term, systemic	200 mg/m3 (not defined)	

#### · PNECs

#### 67-64-1 acetone

freshwater
marine water
sewage treatment plant
sediment, dry weight, freshwater
soil, dry weight
freshwater
soil, dry weight
10.6 mg/l (not defined)
1.06 mg/l (not defined)
30.4 mg/Kg (not defined)
30.4 mg/Kg (not defined)
0.112 mg/Kg (not defined)

Additional information: The lists that were valid during the compilation were used as basis.

#### · 8.2 Exposure controls

· Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures

Avoid contact with the eyes.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

#### · Breathing equipment:

Filter AX.

Not neccessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

(Contd. on page 5)



Page 5/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.12.2024

Version number 5 (replaces version 3)

Revision: 05.12.2024

# Trade name: Signum metal bond I

(Contd. of page 4)

#### · Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Check protective gloves prior to each use for their proper condition.

recommended

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR Nitrile rubber, NBR

- Eye/face protection Tightly sealed safety glasses.
- Body protection:

Protective work clothing.

Light weight protective clothing

### SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information

Physical state
 Colour:
 Smell:
 Acetone-like

· **Odour threshold:** Not determined.
 Not determined

Boiling point or initial boiling point and

boiling range 55 °C

· Flammability Not applicable.

Lower and upper explosion limit

Lower: 2.6 Vol %

· Upper: 13.0 Vol %
· Flash point: -3 °C

Auto-ignition temperature: 465 °C (67-64-1 acetone)

· Decomposition temperature: Not determined.

SADT

· pH at 20 °C 5-6 · Viscosity:

· Kinematic viscosity
Not determined.
· Kinematic viscosity

· dynamic: Not determined.

(Contd. on page 6)



Page 6/10

#### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.12.2024 Version number 5 (replaces version 3) Revision: 05.12.2024

# Trade name: Signum metal bond I

(Contd. of page 5)

Solubility

Water: Not miscible or difficult to mix

· Partition coefficient n-octanol/water (log

Not determined. value)

Steam pressure at 20 °C: 247 hPa

Vapour pressure:

Density and/or relative density

Density Not determined Relative density Not determined. Not determined. · Vapour density

No further relevant information available. · 9.2 Other information

Appearance:

Form: Fluid

· Important information on protection of health

and environment, and on safety.

Self-inflammability: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures is possible.

· Change in condition Not determined. · Evaporation rate

· Information with regard to physical hazard

classes

Void **Explosives** · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void

Flammable liquids Highly flammable liquid and vapour.

· Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void Void

· Oxidising liquids Oxidising solids Void Organic peroxides Void Void Corrosive to metals · Desensitised explosives Void

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
  - Conditions to be avoided: No decomposition if used and stored according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known

(Contd. on page 7)



Page 7/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.12.2024

Version number 5 (replaces version 3)

Revision: 05.12.2024

# Trade name: Signum metal bond I

(Contd. of page 6)

- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None
  - · Additional information: -

### SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
  - · Acute toxicity Based on available data, the classification criteria are not met.

· LD/	· LD/LC50 values that are relevant for classification:		
67-64-1 a	67-64-1 acetone		
Oral	LD50	5,800 mg/kg (rat)	
Dermal	LD50	>15,800 mg/kg (rabbit)	
Inhalative	LC50/4 h	76 mg/l (rat)	
64-19-7 ad	64-19-7 acetic acid		
Oral	LD50	3,310 mg/kg (rat)	
Inhalative	LC50/4 h	11.4 mg/l (rat) (OECD 403)	

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Subacute to chronic toxicity:

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

· 11.2 Information on other hazards

· Endocrine disrupting properties	
128-37-0 2,6-di-tert-butyl-p-cresol	List II

# SECTION 12: Ecological information

· 12.1 Toxicity

	· =··· · · ···························			
· Aquatic t	· Aquatic toxicity:			
67-64-1 acet	67-64-1 acetone			
EC50/48h	8,800 mg/l (daphnia)			
LC50/96h 6,210 mg/l (fish) (OECD 203)				
64-19-7 acet	64-19-7 acetic acid			
EC50/48h	>300.82 mg/l (daphnia) (OECD 202)			
	(Contd. on page 8			

n page ຮ



Page 8/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.12.2024 Version number 5 (replaces version 3) Revision: 05.12.2024

# Trade name: Signum metal bond I

(Contd. of page 7)

LC50/96h >1,000 mg/l (fish) (OECD 203)

ErC50 / 72 h >1,000 mg/l (algae) NOEC / 72h 1,000 mg/l (algae)

NOEC / 96h | 1,000 mg/l (fish) (OECD 203)

#### · 12.2 Persistence and degradability

#### 67-64-1 acetone

Biodegradation 90.9 % /28d (not defined) (OECD 301D)

#### 64-19-7 acetic acid

Biodegradation 96 % /20d (not defined)

- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
  - · PBT: Not applicable.
  - · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

• 12.7 Other adverse effects No further relevant information available.

#### SECTION 13: Disposal considerations

#### · 13.1 Waste treatment methods

Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· Uncleaned packagings:

Recommendation:

Disposal must be made according to official regulations. Non contaminated packagings can be used for recycling.

#### SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1090

14.2 UN proper shipping name

ADR 1090 ACETONE solution
IMDG. IATA ACETONE solution

(Contd. on page 9)



Page 9/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.12.2024

Version number 5 (replaces version 3)

Revision: 05.12.2024

# Trade name: Signum metal bond I

(Contd. of page 8) · 14.3 Transport hazard class(es) ADR · Class 3 (F1) Flammable liquids. · Label · IMDG, IATA ·Class 3 Flammable liquids. · Label · 14.4 Packing group · ADR, IMĎĞ, IATA II· 14.5 Environmental hazards: Marine pollutant: No · 14.6 Special precautions for user Warning: Flammable liquids. Kemler Number: *3*3 F-E,S-D · EMS Number: · Stowage Category · 14.7 Maritime transport in bulk according to IMO instruments Not applicable. · Transport/Additional information: · ADR · Limited quantities (LQ) 1L Excepted quantities (ÉQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · Transport category · Tunnel restriction code D/E · IMDG · Limited quantities (LQ) 1L Excepted quantities (ÉQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml (Contd. on page 10)



Page 10/10

#### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.12.2024

Version number 5 (replaces version 3)

Revision: 05.12.2024

# Trade name: Signum metal bond I

(Contd. of page 9)

UN "Model Regulation":

UN 1090 ACETONE SOLUTION, 3, II

### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
  - Directive 2012/18/EU
    - Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
    - Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- EUH066 Repeated exposure may cause skin dryness or cracking.

#### Abbreviations and acronyms:

SADT: Self Accelerating Decomposition Temperature

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Skin Corr. 1A: Skin corrosion/irritation – Category 1A Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* Data compared to the previous version altered.