



**Safety Data Sheet
according to WHS Regulations**

Printing date 08.07.2024

Version number 4

Revision: 08.07.2024

Hazardous according to criteria of Australian Safety and Compensation Council.

1 Identification

· **Product identifier**

· Trade name: **Signum zirconia bond I**

· **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.

· **Application of the substance / the mixture** Zirconia-Resin Bonding System

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**
Kulzer Australia Pty Ltd
Unit 20, 53 Lorraine St
PEAKHURST NSW 2210
Australia

Tel: +61 (02) 9153 0311

· **Informing department:** see above

· **Emergency telephone number:**
Poison Information Number: Australia 13 11 26 & New Zealand 0800 764 766

2 Hazard(s) Identification

· **Classification of the substance or mixture**

Flam. Liq. 2

H225 Highly flammable liquid and vapour.

Serious eye damage/irritation – Category 2A H319 Causes serious eye irritation.

STOT SE 3

H336 May cause drowsiness or dizziness.

· **Label elements**

· **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Danger

· **Hazard statements**

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear protective gloves / eye protection.

If eye irritation persists: Get medical advice/attention.

· **Other hazards -**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

(Contd. on page 2)



Safety Data Sheet
according to WHS Regulations

Printing date 08.07.2024

Version number 4

Revision: 08.07.2024

Trade name: Signum zirconia bond I

· **vPvB:** Not applicable.

(Contd. of page 1)

3 Composition and Information on Ingredients

· **Chemical characterisation: Mixtures**

· **Description:** -

· **Dangerous components:**

67-64-1	acetone Flam. Liq. 2, H225 Serious eye damage/irritation – Category 2A, H319; STOT SE 3, H336	>90%
85590-00-7	10-(Phosphonoxy)decyl methacrylate Skin Irrit. 2, H315; Serious eye damage/irritation – Category 2A, H319; STOT SE 3, H335	0-5%
64-19-7	acetic acid Flam. Liq. 3, H226 Skin Corr. 1A, H314; Eye Dam. 1, H318 Specific concentration limits: Skin Corr. 1A; H314: $C \geq 90 \%$ Skin Corr. 1B; H314: $25 \% \leq C < 90 \%$ Skin Irrit. 2; H315: $10 \% \leq C < 25 \%$ Eye Irrit. 2; H319: $10 \% \leq C < 25 \%$	≥ 1 -<3%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

· **After inhalation** Supply fresh air; consult doctor in case of symptoms.

· **After skin contact**

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact** Rinse opened eye for several minutes under running water. Then consult doctor.

· **After swallowing**

Rinse out mouth and then drink plenty of water.

In case of persistent symptoms consult doctor.

· **Information for doctor**

· **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire Fighting Measures

· **Suitable extinguishing agents**

CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

· **For safety reasons unsuitable extinguishing agents** Water with a full water jet.

· **Special hazards arising from the substance or mixture**

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

(Contd. on page 3)



**Safety Data Sheet
according to WHS Regulations**

Printing date 08.07.2024

Version number 4

Revision: 08.07.2024

Trade name: Signum zirconia bond I

(Contd. of page 2)

- **Protective equipment:**
Wear self-contained breathing apparatus.
Wear full protective suit.
- **Additional information -**

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures**
Avoid contact with eyes and skin.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Prevent material from reaching sewage system, holes and cellars.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).
Ensure adequate ventilation.
Send for recovery or disposal in suitable containers.
- **Reference to other sections**
See Section 13 for information on disposal.
See Section 8 for information on personal protection equipment.
-

7 Handling and Storage

- **Handling**
 - **Precautions for safe handling**
Keep containers tightly sealed.
Ensure good ventilation/exhaustion at the workplace.
 - **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage**
 - **Requirements to be met by storerooms and containers:** Store in cool location.
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:**
Store in cool, dry conditions in well sealed containers.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Components with critical values that require monitoring at the workplace:**

67-64-1 acetone

WES Short-term value: 2375 mg/m³, 1000 ppm
Long-term value: 1185 mg/m³, 500 ppm

64-19-7 acetic acid

WES Short-term value: 37 mg/m³, 15 ppm
Long-term value: 25 mg/m³, 10 ppm

(Contd. on page 4)



Safety Data Sheet
according to WHS Regulations

Printing date 08.07.2024

Version number 4

Revision: 08.07.2024

Trade name: Signum zirconia bond I

(Contd. of page 3)

· DNELs		
67-64-1 acetone		
Oral	general population, long term, systemic	62 mg/Kg (not defined)
Dermal	worker industrial, long term, systemic	186 mg/Kg/d (not defined)
	general population, long term, systemic	62 mg/Kg/d (not defined)
Inhalative	worker industrial, long term, systemic	1,210 mg/m ³ (not defined)
	worker industrial, long term, local	2,420 mg/m ³ (not defined)
	general population, long term, systemic	200 mg/m ³ (not defined)

· PNECs	
67-64-1 acetone	
freshwater	10.6 mg/l (not defined)
marine water	1.06 mg/l (rabbit)
sewage treatment plant	19.5 mg/l (not defined)
sediment, dry weight, freshwater	30.4 mg/Kg (not defined)
sediment, dry weight, marine water	3.04 mg/Kg (not defined)
soil, dry weight	0.112 mg/Kg (not defined)

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **Personal protective equipment**

· **General protective and hygienic measures**

- Avoid contact with the eyes.
- Keep away from foodstuffs, beverages and food.
- Instantly remove any soiled and impregnated garments.
- Wash hands during breaks and at the end of the work.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

Not necessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Check protective gloves prior to each use for their proper condition.
recommended

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

- Butyl rubber, BR
- Nitrile rubber, NBR

(Contd. on page 5)



Safety Data Sheet
according to WHS Regulations

Printing date 08.07.2024

Version number 4

Revision: 08.07.2024

Trade name: Signum zirconia bond I

(Contd. of page 4)

- **Eye protection:** Tightly sealed safety glasses.
- **Body protection:** Protective work clothing.

9 Physical and Chemical Properties

- **General Information**
 - **Appearance:**
 - **Form:** Fluid
 - **Colour:** Colourless
 - **Smell:** Acetone-like
 - **Odour threshold:** Not determined.
- **pH-value:** Mixture is non-soluble (in water).
- **Change in condition**
 - **Melting point/freezing point:** Not determined
 - **Initial boiling point and boiling range:** 55 °C
- **Flash point:** -19 °C
- **Inflammability (solid, gaseous)** Not applicable.
- **Auto-ignition temperature:** 465 °C
 - **Decomposition temperature:** Not determined.
- **Self-inflammability:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures is possible.
- **Critical values for explosion:**
 - **Lower:** 2.6 Vol %
 - **Upper:** 13.0 Vol %
- **Steam pressure at 20 °C:** 247 hPa
- **Density** Not determined
 - **Relative density** Not determined.
 - **Vapour density** Not determined.
 - **Evaporation rate** Not determined.
- **Solubility in / Miscibility with**
 - **Water:** Not miscible or difficult to mix
- **Partition coefficient: n-octanol/water:** Not determined.
- **Viscosity:**
 - **dynamic:** Not determined.
 - **kinematic:** Not determined.
- **Other information** No further relevant information available.

10 Stability and Reactivity

- **Reactivity** No further relevant information available.
- **Conditions to be avoided:** No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** None

(Contd. on page 6)

AU



**Safety Data Sheet
according to WHS Regulations**

Printing date 08.07.2024

Version number 4

Revision: 08.07.2024

Trade name: Signum zirconia bond I

· **Additional information:** -

(Contd. of page 5)

11 Toxicological Information

· **Information on toxicological effects**

· **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

67-64-1 acetone

Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	>15,800 mg/kg (rabbit)
Inhalative	LC50/4 h	76 mg/l (rat)

64-19-7 acetic acid

Oral	LD50	3,310 mg/kg (rat)
Inhalative	LC50/4 h	11.4 mg/l (rat) (OECD 403)

· **Skin corrosion/irritation** Based on available data, the classification criteria are not met.

· **Serious eye damage/irritation**

Causes serious eye irritation.

· **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

· **Carcinogenicity** Based on available data, the classification criteria are not met.

· **Reproductive toxicity** Based on available data, the classification criteria are not met.

· **STOT-single exposure**

May cause drowsiness or dizziness.

· **STOT-repeated exposure** Based on available data, the classification criteria are not met.

· **Aspiration hazard** Based on available data, the classification criteria are not met.

· **Subacute to chronic toxicity:**

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

12 Ecological Information

· **Toxicity**

· **Aquatic toxicity:**

67-64-1 acetone

EC50/48h	8,800 mg/l (daphnia)
LC50/96h	6,210 mg/l (fish) (OECD 203)

64-19-7 acetic acid

EC50/48h	>300.82 mg/l (daphnia) (OECD 202)
LC50/96h	>1,000 mg/l (fish) (OECD 203)
ErC50 / 72 h	>1,000 mg/l (algae)
NOEC / 72h	1,000 mg/l (algae)
NOEC / 96h	1,000 mg/l (fish) (OECD 203)

(Contd. on page 7)



Safety Data Sheet
according to WHS Regulations

Printing date 08.07.2024

Version number 4

Revision: 08.07.2024

Trade name: Signum zirconia bond I

(Contd. of page 6)

· **Persistence and degradability**

67-64-1 acetone

Biodegradation 90.9 % /28d (not defined) (OECD 301D)

64-19-7 acetic acid

Biodegradation 96 % /20d (not defined)

· **Behaviour in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· **Uncleaned packagings:**

· **Recommendation:**

Disposal must be made according to official regulations.
Non contaminated packagings can be used for recycling.

14 Transport information

· **UN-Number**

· **ADG, IMDG, IATA**

UN1090

· **UN proper shipping name**

· **ADG**
· **IMDG, IATA**

1090 ACETONE solution
ACETONE solution

· **Transport hazard class(es)**

· **ADG**



· **Class**

3 (F1) Flammable liquids.

(Contd. on page 8)

AU



Safety Data Sheet
according to WHS Regulations


Printing date 08.07.2024

Version number 4

Revision: 08.07.2024

Trade name: Signum zirconia bond I

(Contd. of page 7)

· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· Packing group	
· ADG, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids.
· Kehler Number:	33
· EMS Number:	F-E,S-D
· Stowage Category	E
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	-
· ADG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1090 ACETONE SOLUTION, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Industrial Chemicals	
67-64-1	acetone
64-19-7	acetic acid
128-37-0	2,6-di-tert-butyl-p-cresol

(Contd. on page 9)



**Safety Data Sheet
according to WHS Regulations**

Printing date 08.07.2024

Version number 4

Revision: 08.07.2024

Trade name: Signum zirconia bond I

(Contd. of page 8)

· **Australia: Priority Existing Chemicals**

None of the ingredients is listed.

· **Directive 2012/18/EU**

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5.000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50.000 t

· **National regulations**

The product is subject to classification in accordance with the prevailing version of the regulations on hazardous materials.

· **Other regulations, limitations and prohibitive regulations**

· **AICS - Australian Inventory of Chemical Substances**

67-64-1 acetone

64-19-7 acetic acid

128-37-0 2,6-di-tert-butyl-p-cresol

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

· **Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Skin Corr. 1A: Skin corrosion/irritation – Category 1A
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Dam. 1: Serious eye damage/eye irritation – Category 1
- Serious eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· *** Data compared to the previous version altered.**