



**Safety Data Sheet  
according to WHS Regulations**

Printing date 17.11.2022

Version number 4

Revision: 17.11.2022

Hazardous according to criteria of Australian Safety and Compensation Council.

## 1 Identification

· **Product identifier**

· **Trade name:** **Signum composite flow**

· **Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.

· **Application of the substance / the mixture** Veneering resin

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Kulzer Australia Pty Ltd  
Unit 20, 53 Lorraine St  
PEAKHURST NSW 2210  
Australia

Tel: +61 (02) 9153 0311

· **Informing department:** see above

· **Emergency telephone number:**

Poison Information Number: Australia 13 11 26 & New Zealand 0800 764 766

## 2 Hazard(s) Identification

· **Classification of the substance or mixture**

Skin Sens. 1 H317 May cause an allergic skin reaction.

· **Label elements**

· **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS07

· **Signal word** Warning

· **Hazard-determining components of labelling:**

triethylen glycol dimethacrylate

· **Hazard statements**

May cause an allergic skin reaction.

· **Precautionary statements**

Wear protective gloves/protective clothing/eye protection/face protection.

If skin irritation or rash occurs: Get medical advice/attention.

· **Other hazards -**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

## 3 Composition and Information on Ingredients

· **Chemical characterisation:** Mixtures

· **Description:** -

(Contd. on page 2)



**Safety Data Sheet  
according to WHS Regulations**

Printing date 17.11.2022

Version number 4

Revision: 17.11.2022

**Trade name: Signum composite flow**

(Contd. of page 1)

**· Dangerous components:**

109-16-0	triethylen glycol dimethacrylate Skin Sens. 1B, H317	≥10-≤25%
80-62-6	methyl methacrylate Flam. Liq. 2, H225 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	≥0.1-<1%

**· Additional information** For the wording of the listed hazard phrases refer to section 16.

#### 4 First Aid Measures

**· Description of first aid measures**

· **After inhalation** Supply fresh air; consult doctor in case of symptoms.

· **After skin contact**

Instantly wash with water and soap and rinse thoroughly.  
If skin irritation continues, consult a doctor.

· **After eye contact**

Rinse opened eye for several minutes under running water. Then consult doctor.

· **After swallowing**

Rinse out mouth and then drink plenty of water.  
In case of persistent symptoms consult doctor.

· **Information for doctor**

· **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

#### 5 Fire Fighting Measures

· **Extinguishing media**

· **Suitable extinguishing agents**

CO<sub>2</sub>, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.  
Use fire fighting measures that suit the environment.

· **Special hazards arising from the substance or mixture** No further relevant information available.

· **Advice for firefighters**

· **Protective equipment:** No special measures required.

· **Additional information** -

#### 6 Accidental Release Measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective clothing.

· **Environmental precautions:**

Do not allow product to reach sewage system or water bodies.  
Do not allow to enter the ground/soil.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).  
Send for recovery or disposal in suitable containers.

· **Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

(Contd. on page 3)



**Safety Data Sheet  
according to WHS Regulations**

Printing date 17.11.2022

Version number 4

Revision: 17.11.2022

**Trade name: Signum composite flow**

(Contd. of page 2)

**7 Handling and Storage**

- **Handling**
  - **Precautions for safe handling** Wear protective equipment. Keep unprotected persons away.
  - **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
  - **Storage**
    - **Requirements to be met by storerooms and containers:** No special requirements.
    - **Information about storage in one common storage facility:** Not required.
    - **Further information about storage conditions:** None.
  - **Specific end use(s)** No further relevant information available.

**8 Exposure controls and personal protection**

· **Control parameters**

· **Components with critical values that require monitoring at the workplace:**

**80-62-6 methyl methacrylate**

WES	Short-term value: 416 mg/m <sup>3</sup> , 100 ppm Long-term value: 208 mg/m <sup>3</sup> , 50 ppm Sen
-----	-------------------------------------------------------------------------------------------------------------

· **DNELs**

**109-16-0 triethylen glycol dimethacrylate**

Oral	general population, long term, systemic	8.33 mg/Kg (not defined)
Dermal	worker industrial, long term, systemic	13.9 mg/Kg/d (not defined)
	general population, long term, systemic	8.33 mg/Kg/d (not defined)
Inhalative	general population, long term, systemic	8.33 mg/Kg/d (not defined)
	worker industrial, long term, systemic	48.5 mg/m <sup>3</sup> (not defined)
	general population, long term, systemic	14.5 mg/m <sup>3</sup> (not defined)

**41637-38-1 bisphenol a polyethylene glycol diether dimethacrylate**

Oral	general population, long term, systemic	5 mg/Kg (not defined)
Dermal	worker industrial, long term, systemic	140 mg/Kg/d (not defined)
	general population, long term, systemic	50 mg/Kg/d (not defined)
Inhalative	worker industrial, long term, systemic	98.7 mg/m <sup>3</sup> (not defined)
	general population, long term, systemic	17.4 mg/m <sup>3</sup> (not defined)

**131-57-7 Oxybenzone**

Oral	general population, long term, systemic	2 mg/Kg (not defined)
Dermal	worker industrial, long term, systemic	39 mg/Kg/d (not defined)
	general population, long term, systemic	20 mg/Kg/d (not defined)
Inhalative	worker industrial, long term, systemic	27.7 mg/m <sup>3</sup> (not defined)
	general population, long term, systemic	6.8 mg/m <sup>3</sup> (not defined)

**80-62-6 methyl methacrylate**

Oral	general population, long term, systemic	8.2 mg/Kg (not defined)
Dermal	worker industrial, long term, systemic	13.67 mg/Kg/d (not defined)
	general population, long term, systemic	8.2 mg/Kg/d (not defined)

(Contd. on page 4)



**Safety Data Sheet  
according to WHS Regulations**

Printing date 17.11.2022

Version number 4

Revision: 17.11.2022

**Trade name: Signum composite flow**

(Contd. of page 3)

<i>Inhalative</i>	<i>worker industrial, acute, local</i>	416 mg/m <sup>3</sup> (not defined)
	<i>worker industrial, long term, systemic</i>	348.4 mg/m <sup>3</sup> (not defined)
	<i>worker industrial, long term, local</i>	208 mg/m <sup>3</sup> (not defined)
	<i>general population, acute, local</i>	208 mg/m <sup>3</sup> (not defined)
	<i>general population, long term, systemic</i>	74.3 mg/m <sup>3</sup> (not defined)

**· PNECs**

**109-16-0 triethylen glycol dimethacrylate**

<i>freshwater</i>	0.016 mg/l (not defined)
<i>marine water</i>	0.002 mg/l (not defined)
<i>sewage treatment plant</i>	1.7 mg/l (not defined)
<i>sediment, dry weight, freshwater</i>	0.185 mg/Kg (not defined)
<i>sediment, dry weight, marine water</i>	0.018 mg/Kg (not defined)
<i>soil, dry weight</i>	0.027 mg/Kg (not defined)

**131-57-7 Oxybenzone**

<i>freshwater</i>	0.00067 mg/l (not defined)
<i>marine water</i>	0.000067 mg/l (not defined)
<i>sewage treatment plant</i>	10 mg/l (not defined)
<i>sediment, dry weight, freshwater</i>	0.066 mg/Kg (not defined)
<i>sediment, dry weight, marine water</i>	0.007 mg/Kg (not defined)
<i>soil, dry weight</i>	0.013 mg/Kg (not defined)

**80-62-6 methyl methacrylate**

<i>freshwater</i>	0.94 mg/l (not defined)
<i>marine water</i>	0.094 mg/l (not defined)
<i>sewage treatment plant</i>	10 mg/l (not defined)
<i>sediment, dry weight, freshwater</i>	10.2 mg/Kg (not defined)
<i>sediment, dry weight, marine water</i>	0.102 mg/Kg (not defined)
<i>soil, dry weight</i>	1.48 mg/Kg (not defined)

**· Additional information:** The lists that were valid during the compilation were used as basis.

**· Exposure controls**

**· Personal protective equipment**

**· General protective and hygienic measures**

*Wash hands during breaks and at the end of the work.*

**· Breathing equipment:** *Not necessary if room is well-ventilated.*

**· Protection of hands:**

*Check protective gloves prior to each use for their proper condition. recommended*

**· Material of gloves**

*The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*

**· Penetration time of glove material**

*The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.*

**· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

*Butyl rubber, BR  
Nitrile rubber, NBR*

(Contd. on page 5)



**Safety Data Sheet**  
**according to WHS Regulations**

Printing date 17.11.2022

Version number 4

Revision: 17.11.2022

**Trade name: Signum composite flow**

- **Eye protection:** Safety glasses
- **Body protection:** Light weight protective clothing

(Contd. of page 4)

**9 Physical and Chemical Properties**

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

- **Form:** Fluid
- **Colour:** Brown  
White  
Pink  
Colourless

- **Smell:** Odourless
- **Odour threshold:** Not determined.

- **pH-value:** Mixture is non-soluble (in water).

· **Change in condition**

- **Melting point/freezing point:** Not determined
- **Initial boiling point and boiling range:** 255 °C

- **Flash point:** >100 °C

- **Inflammability (solid, gaseous)** Not applicable.

- **Decomposition temperature:** Not determined.

- **Self-inflammability:** Product is not selfigniting.

- **Explosive properties:** Product is not explosive.  
Not determined.

· **Critical values for explosion:**

- **Lower:** Not determined.
- **Upper:** Not determined.

- **Steam pressure:** Not determined.

- **Density** Not determined

- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

- **Water:** Not miscible or difficult to mix

- **Partition coefficient: n-octanol/water:** Not determined.

· **Viscosity:**

- **dynamic:** Not determined.
- **kinematic:** Not determined.

· **Solvent content:**

- **Water:** 1.3 %

- **Solids content:** 9.6 %

- **Other information** No further relevant information available.

AU  
(Contd. on page 6)



**Safety Data Sheet  
according to WHS Regulations**

Printing date 17.11.2022

Version number 4

Revision: 17.11.2022

**Trade name: Signum composite flow**

(Contd. of page 5)

**10 Stability and Reactivity**

- **Reactivity** No further relevant information available.
- **Chemical stability**
  - **Conditions to be avoided:** No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** None
- **Additional information:** -

**11 Toxicological Information**

- **Information on toxicological effects**

- **Acute toxicity**

- **LD/LC50 values that are relevant for classification:**

**109-16-0 triethylen glycol dimethacrylate**

Oral	LD50	8,300 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (mouse)

**68611-44-9 Silane, dichlorodimethyl-, reaction products with silica**

Oral	LD50	>5,000 mg/kg (rat)
Inhalative	LC0/4h	0.477 mg/L (rat)

**41637-38-1 bisphenol a polyethylene glycol diether dimethacrylate**

Oral	LD50	>2,000 mg/kg (rat) (OECD 423)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)

**131-57-7 Oxybenzone**

Oral	LD50	>12,800 mg/kg (rat) (OECD 401)
Dermal	LD50	>16,000 mg/kg (rabbit) (OECD 402)

**80-62-6 methyl methacrylate**

Oral	LD50	~7,900 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (guinea pig) (OECD 402)
Inhalative	LC50/4 h	29.8 mg/l (rat)

- **Respiratory or skin sensitisation** No sensitizing effect known.
- **Additional toxicological information:**
  - **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
  - **Reproductive toxicity** Based on available data, the classification criteria are not met.

**12 Ecological Information**

- **Toxicity**

- **Aquatic toxicity:**

**65997-17-3 Glaspulver**

EC50/72h	>1,000 mg/l (daphnia)
LC50/96h	>1,000 mg/l (fish)
ErC50 / 72 h	>1,000 mg/l (algae)
NOEC / 72h	1,000 mg/l (algae)
	1,000 mg/l (daphnia)

(Contd. on page 7)



**Safety Data Sheet  
according to WHS Regulations**

Printing date 17.11.2022

Version number 4

Revision: 17.11.2022

**Trade name: Signum composite flow**

(Contd. of page 6)

**109-16-0 triethylen glycol dimethacrylate**

EC50/21d	51.9 mg/L (daphnia) (OECD 211)
LC50/96h	16.4 mg/l (fish) (OECD 203)
NOEC / 21d	32 mg/l (daphnia) (OECD 211)
ErC50 / 72 h	>100 mg/l (algae) (OECD 201)
NOEC / 72h	18.6 mg/l (algae) (OECD 201)
EbC50 / 72h	72.8 mg/l (algae) (OECD 201)

**68611-44-9 Silane, dichlorodimethyl-, reaction products with silica**

LC50/96h	>10,000 mg/l (fish) (OECD 203)
ErC50 / 72 h	>10,000 mg/l (algae) (OECD 201)
EC50 / 24h	>10,000 mg/l (daphnia) (OECD 202)

**41637-38-1 bisphenol a polyethylene glycol diether dimethacrylate**

LL50/96h	>100 mg/L (fish) (OECD 203)
EL50/48h	>100 mg/L (daphnia) (OECD 202)
EL50/72h	>100 mg/L (algae) (OECD 201)
NOEC / 21d	≥0.00224 mg/l (daphnia) (OECD 211)

**131-57-7 Oxybenzone**

EC50/48h	1.87 mg/l (daphnia) (OECD 202)
LC50/96h	3.8 mg/l (fish) (OECD 203)
ErC50 / 72 h	0.67 mg/l (algae) (OECD 201)
NOEC / 72h	0.18 mg/l (algae) (OECD 201)
NOEC / 96h	0.72 mg/l (fish) (OECD 203)
NOEC / 48h	1.15 mg/l (daphnia) (OECD 202)

**80-62-6 methyl methacrylate**

EC50/21d	49 mg/L (daphnia) (OECD 211)
EC50/48h	69 mg/l (daphnia) (EPA OTS 797.1300)
NOEC / 21d	37 mg/l (daphnia) (OECD 211)
ErC50 / 72 h	>110 mg/l (algae) (OECD 201)
NOEC / 72h	110 mg/l (algae) (OECD 201)
NOEC / 48h	48 mg/l (daphnia) (EPA OTS 797.1300)
EbC50 / 72h	>110 mg/l (algae) (OECD 201)
NOEC/ 35d	9.4 mg/L (fish) (OECD 210)
LC50/ 35d	33.7 mg/L (fish) (OECD 210)

**Persistence and degradability**

**109-16-0 triethylen glycol dimethacrylate**

Biodegradation	85 % /28d (not defined) (OECD 301B; ISO/ 9439/ EEC 92/69/V, C.4-C)
----------------	--------------------------------------------------------------------

**41637-38-1 bisphenol a polyethylene glycol diether dimethacrylate**

Biodegradation	24 % /28d (not defined) (OECD 301D)
----------------	-------------------------------------

**131-57-7 Oxybenzone**

Biodegradation	60-70 % /28d (not defined)
----------------	----------------------------

**80-62-6 methyl methacrylate**

Biodegradation	94 % /14d (not defined) (OECD 301C)
----------------	-------------------------------------

(Contd. on page 8)



**Safety Data Sheet  
according to WHS Regulations**

Printing date 17.11.2022

Version number 4

Revision: 17.11.2022

**Trade name: Signum composite flow**

(Contd. of page 7)

**Behaviour in environmental systems:**

**Bioaccumulative potential**

**131-57-7 Oxybenzone**

Bloconcentration factor (BCF) >33-<160 (fish) (OECD 305)

**Mobility in soil** No further relevant information available.

**Ecotoxicological effects:**

**Remark:** Harmful to fish

**Additional ecological information:**

**General notes:**

Avoid transfer into the environment.

Harmful to aquatic organisms

**Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**Other adverse effects** No further relevant information available.

**13 Disposal considerations**

**Waste treatment methods**

**Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

**Uncleaned packagings:**

**Recommendation:**

Disposal must be made according to official regulations.

Non contaminated packagings can be used for recycling.

**14 Transport information**

**UN-Number**

**ADG, ADN, IMDG, IATA**

Void

**UN proper shipping name**

**ADG, ADN, IMDG, IATA**

Void

**Transport hazard class(es)**

**ADG, ADN, IMDG, IATA**

**Class**

Void

**Packing group**

**ADG, IMDG, IATA**

Void

**Environmental hazards:**

Not applicable.

**Special precautions for user**

Not applicable.

**Transport in bulk according to Annex II of  
Marpol and the IBC Code**

Not applicable.

**Transport/Additional information:**

-

(Contd. on page 9)





**Safety Data Sheet  
according to WHS Regulations**

Printing date 17.11.2022

Version number 4

Revision: 17.11.2022

**Trade name: Signum composite flow**

(Contd. of page 8)

· **UN "Model Regulation":** Void

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
  - **Directive 2012/18/EU**
    - **Named dangerous substances - ANNEX I** None of the ingredients is listed.
  - **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

- **\* Data compared to the previous version altered.**